



240 Series Flareless Fittings



STRAIGHT

Flareless fittings - mates with AS33514 / AS4375 and AS33515 / AS4377 (straight)


Hose	S/S Fitting	A REF	B MAX	C REF	D MAX	F REF GAGE PT	THREAD SIZE	MATERIAL WT (LB) REF
SS								
R160-4	Y40404-72	.320	1.36	.562	.55	.155	.4375-20	.07
R160-6	Y40406-72	.326	1.52	.688	.69	.164	.5625-18	.09
R160-8	Y40408-72	.368	1.68	.875	.81	.189	.7500-16	.17
R160-10	Y40410-72	.396	1.79	1.000	.93	.201	.8750-14	.23
R160-12	Y40412-72	.421	2.05	1.250	1.19	.228	1.0625-12	.40
R160-16	Y40416-72	.425	2.45	1.500	1.63	.297	1.3125-12	.63
R160-20	Y40420-72	.452	2.99	1.812	2.06	.300	1.6250-12	1.42
R160-24	Y40424-72	.765	3.50	2.125	2.46	.365	1.8750-12	2.06



45° ELBOW

Flareless fittings - mates with AS33514 / AS 4375 and AS33515 / AS4377 (45° elbow)

Hose	S/S Fitting#	A REF	B MAX	C REF	D MAX	E NOM	F REF	THREAD SIZE	MATERIAL WT (LB) REF
SS									
R160-4	Y40504-72	.320	1.95	.562	.54	.419	.110	.4375-20	.07
R160-6	Y40506-72	.326	2.10	.688	.63	.544	.116	.5625-18	.12
R160-8	Y40508-72	.368	2.37	.875	.75	.602	.134	.7500-16	.19
R160-10	Y40510-72	.396	2.64	1.000	.87	.735	.142	.8750-14	.27
R160-12	Y40512-72	.421	3.06	1.250	1.13	.735	.161	1.0625-12	.46
R160-16	Y40516-72	.425	3.84	1.500	1.45	.936	.210	1.3125-12	.81



90° ELBOW

Flareless fittings - mates with AS33514 / AS4375 and AS33515 / AS4377 (90° elbow)

Hose	S/S Fitting#	A REF	B MAX	C REF	D MAX	E NOM	F REF	THREAD SIZE	MATERIAL WT (LB) REF
SS									
R160-4	Y40604-72	.320	1.47	.562	.54	.744	.155	.4375-20	.07
R160-6	Y40606-72	.326	1.79	.688	.63	.995	.164	.5625-18	.12
R160-8	Y40608-72	.368	2.07	.875	.75	1.149	.189	.7500-16	.20
R160-10	Y40610-72	.396	2.23	1.000	.87	1.411	.201	.8750-14	.29
R160-12	Y40612-72	.421	2.80	1.250	1.13	1.485	.228	1.0625-12	.50
R160-16	Y40616-72	.425	3.52	1.500	1.45	1.914	.297	1.3125-12	.83

Unless otherwise specified, all dimensions are in inches.